

Shenzhen, China

RoHS, CE, FCC, SGS

Skymen

JP-240G

Negotiation

In Stock

JP-240G

T/T

Wooden case

800 pcs per month

1

Block / Gear Industrial Ultrasonic Cleaner 80L 1200W With Filtration Cycle System

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

- Model:
- Tank Volume:
- Ultrasonic Power:
- Heating Power:
- Frequency:
- Internal Tank Size:
- Filter Cycle System:
- Gross Weight:
- Highlight:

77L 1200W 3000W 40KHz/28KHz 550X400X350mm (L*W*H) 1 Set

140KG

automotive ultrasonic cleaner, ultrasonic washing machine



More Images



Our Product Introduction

Product Description

80L Ultrasonic Cleaner 1200W for Block, Gear with Filtration Cycle System 28/40KHz

| Specification | | | | |
|----------------------------|--|--|--|--|
| Model | JP-240G | | | |
| Tank Volume | 77L | | | |
| Internal tank size | 550X400X350mm | | | |
| Transducers | 24pcs 50W of every transducer | | | |
| Ultrasonic Power | 1200W | | | |
| Heating Power | 3000W | | | |
| Frenquency | 28KHz/40KHz | | | |
| Filtration Cycle System | 1 set | | | |
| Unit size | 780*1050*805mm | | | |
| Packing size | 840*1110*925mm | | | |
| Timer | 0~99 minutes adjustable | | | |
| Heater | Room temperature~99 adjustable | | | |
| Material | SUS 304 default, can be SUS 316 | | | |
| Power Supply | AC 110V ; AC 220V | | | |
| N.W. | 125KG | | | |
| G.W. | 140KG Wrapped by film in wooden case | | | |
| Lead time | 12 working days | | | |
| Warranty | 1 year warranty period, technique support all time | | | |
| Certificates | CE, RoHS, FCC, SGS | | | |
| Advantage | Filter the dirty water; keep the water clear in tank; lower the frequency of changing water | | | |

Same series with different size:

| Model | Tank size | Volume | Ultrasoni c Power | Heating Power | Transducer |
|----------|-------------------|--------|-------------------------|------------------|------------|
| | L*W*H (mm) | (L) | (W) | (W) | (pcs) |
| JP-120G | 500X300X25 0 | 38L | 600W | 1500W | 12pcs |
| JP-180G | 500X350X30 0 | 53L | 900W | 1500W | 18pcs |
| JP-240G | 550X400X35 0 | 77L | 1200W | 3000W | 24pcs |
| JP-300G | 550X450X40 0 | 99L | 1500W | 3000W | 30pcs |
| JP-301G | 800X300X40 0 | 96L | 1500W | 3000W | 30pcs |
| JP-360G | 600X500X45 0 | 135L | 1800W | 4500W | 36pcs |
| JP-480G | 700X500X50 0 | 175L | 2400W | 6000W | 48pcs |
| JP-600G | 800X600X55 0 | 246L | 3000W | 6000W | 60pcs |
| JP-720G | 1000X600X6 00 | 360L | 3600W | 9000W | 72pcs |
| JP-1108G | 1000X900X6 00 | 540L | 5400W | 18000W | 108pcs |
| JP-1144G | 1200X1000X 800 | 960L | 7200W | 27000W | 144pcs |

Images:





Clean effect:





Oil Filters for cleaning



Cleaned oil filters with Light passing through



Features:

Fully insulated stainless steel tank construction; Digital LED screen show temp and time, easy to use; Adjustable built-in heat to improve the cleaning effectiveness; Stainless steel lid help to reduce the noise;

Principle:

The principle of the ultrasonic cleaning machine is mainly to convert the sound energy of the power ultrasonic frequency source into mechanical vibration through the transducer, and to irradiate the ultrasonic wave into the cleaning liquid in the groove through the cleaning tank wall. Due to the radiation of the ultrasonic waves, the microbubbles in the liquid in the tank can be kept vibrated by the action of the sound waves. The adsorption of the dirt and the surface of the cleaning member is destroyed, causing fatigue damage of the dirt layer to be rejected, and the vibration of the gas type bubble scrubs the solid surface.

