

## JP-3036GH Industrial Ultrasonic Cleaner 60pcs Transducers For DPF Car Parts Hardware

Our Product Introduction

for more products please visit us on [skymenultrasonic.com](http://skymenultrasonic.com)

### Basic Information

- Place of Origin: China
- Brand Name: skymen/OEM
- Certification: CE/FCC/RHoS/REACH
- Model Number: JP-3060GH
- Minimum Order Quantity: 1 unit
- Price: Negotiation
- Packaging Details: wooden case
- Delivery Time: In Stock
- Payment Terms: T/T, L/C, Paypal
- Supply Ability: 5000 units per week

#### Display Chart

Simple Operation Panel Equipped With Inlet And Drainage Valves



### Product Specification

- Tank Capacity: 99L
- Tank Size: 550X450X400 Mm
- Ultrasonic Power: 1500W For Two
- Heating Power: 4500W For Two
- Frequency: 40KHz / 28KHz
- Transducer: 60pcs
- Highlight: Car Parts Industrial Ultrasonic Cleaner, 60pcs Transducers Industrial Ultrasonic Cleaner, 99L Car Parts Ultrasonic Cleaner

#### Upgrade Interface


ULTRASONIC CLEANER



01  
Button Or PLC Control  
Selectable

02  
Drain Valve

Equipped With Inlet  
And Drainage Valves




03  
Cylinder head  
concave design

Cylinder head concave  
design-Beautiful  
Tight handle Lid

### More Images



07  
Universal Casters  
Universal Casters  
Convenient For Moving



08  
Generator  
Independent research  
and development of  
ultrasonic generator  
Stable Output

## Product Description

### 1500W\*2 99L Capacity JP-3060GH Industrial Ultrasonic Cleaner

**Function:**

Ultrasound is the most efficient and cost effective method of removing Carbon ,oil, rust ,build-up dirt .

**Features:**

Dirt and oil could be removed in a short time by using the strong cavitation of ultrasound.

Time is adjustable among 1 second to 500 hours by simple handle of large timer.

Additional special case for small parts cleaning and drainage for changing of cleaning solution.

Automatic stopwatch to manage working time and maintenance time.

Standard residual-current circuit breaker: used for testing leakage power. And keeping moving of machine and cutting of power switch.

**Specificatoin:**

Model	JP-3060GH
Ultrasonic power	1500W*2 (60pcs transducers)
Frequency	40KHz / 28KHz
Housing material	SUS304
Tank material	SUS304 / 316
Heating power	4500W*2
Tank capacity	99L
Timer	Digital 1-99 min adjustable
Heater	Room temperature~150°C
Voltage	AC 380V, 3phase 50Hz
Tank size	550X450X400mm
Certificate	ISO9001:2008 CE & RoHS

**From 10 galles to 200 gallons , size could be customized**

**Images of this model:**

# Three Tanks Ultrasonic Cleaning Machine

## ULTRASONIC CLEANER



### Similar models with different tank volume:

Model	Tank size	Volume	Ultrasonic Power	Heating Power	Transducer
	L*W*H (mm)	(L)	(W)	(W)	(pcs)
JP-3024GH	500X300X250	38L	600W*2	1500W*2	24pcs
JP-3036GH	500X350X300	53L	900W*2	1500W*2	36pcs
JP-3048GH	550X400X350	77L	1200W*2	3000W*2	48pcs
<b>JP-3060GH</b>	<b>550X450X400</b>	<b>99L</b>	<b>1500W*2</b>	<b>4500W*2</b>	<b>60pcs</b>
JP-3061GH	800X300X400	96L	1500W*2	4500W*2	30pcs
JP-3072GH	600X500X450	135L	1800W*2	4500W*2	72pcs
JP-3096GH	700X500X500	175L	2400W*2	6000W*2	96pcs
JP-3120GH	800X600X550	246L	3000W*2	6000W*2	120pcs
JP-3144GH	1000X600X600	360L	3600W*2	9000W*2	144pcs
JP-3168GH	1500X700X400	420L	4200W*2	15000W*2	168pcs
JP-3192GH	1200X500X800	480L	4800W*2	15000W*2	192pcs
JP-3216GH	1000X900X600	540L	5400W*2	18000W*2	216pcs
JP-3240GH	1000X800X800	640L	6000W*2	21000W*2	240pcs
JP-3264GH	1000X1000X800	800L	6600W*2	24000W*2	264pcs
JP-3288GH	1200X1000X800	960L	7200W*2	27000W*2	288pcs
JP-3432GH	1500X1000X1000	1500L	10800W*2	36000W*2	432pcs


### How does Ultrasonic Cleaner work?

## DIRT ELIMINATION PROCESS THROUGH ULTRASONIC TECHNOLOGY


- Cleaning effect will be much better if using the machine together with proper solvent.



As ultrasonic wave through the solution in the tank, cause alternating high and low pressures in the solution.



During the low pressure stage, millions of microscopic bubbles form and grow. This process is called "CAVITATION".



During the high pressure stage, the bubbles implode releasing enormous amounts of energy. They work in all directions, attacking surface and invading all recesses and openings.

### How to use an ultrasonic cleaner ?

As ultrasonic wave through the solution in the tank, cause alternating high and low pressures in the solution. During the low pressure stage , millions of the microscopic bubbles form and grow . This process is called "CAVITATION" . During the high pressure stage , the bubbles implode releasing enormous amounts of the energy . They work in all directions , attacking surface and invading all recesses and openings.

### Package by polywooden case:

#### Before and after :



**Skymen Technology Corporation Limited**

☎ 86-755-27094405

✉ info@skymen.cc

🌐 skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen